


Technical sheet :

150 AETJ-L BI




Capacities		Metric
Working height	h21	15.4 m
Platform height	h7	13.4 m
Max. outreach	r1	7.81 m
Overhang	h31	7.27 m
Pendular arm rotation (top / bottom)		+70 ° / -70 °
Platform capacity	Q	230 kg
Turret rotation		355 °
Platform rotation (right / left)		70 ° / 70 °
Number of people (inside / outside)		2 / 2
Weight and dimensions		
Platform weight*		6435 kg
Platform dimensions (length x width)	lp / ep	1.2 m x 0.92 m
Overall width	b1	1.91 m
Overall length	l1	6.11 m
Overall height	h17	2.095 m
Overall length (stowed)	l9	4.55 m
Overall height (stowed)	h18	2.13 m
Floor height (access)	h20	0.4 m
Jib length	l13	1.26 m
Counterweight offset (turret at 90°)	a7	0 m
Internal turning radius (over tyres)	b13	1.88 m
External turning radius	Wa3	4.27 m
Tailswing		0 m
Ground clearance at centre of wheelbase	m2	0.185 m
Wheelbase	y	2.2 m
Performances		
Drive speed - stowed		6 km/h
Drive speed - raised		0.6 km/h
Gradeability		23 %
Permissible leveling		5 °
Wheels		
Tyres type		Foam Filled Non Marking
Dimensions of front wheels		0,65x0,25 mm
Drive wheels (front / rear)		0 / 2
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		0 / 2
Engine/Battery		
Electric engine power rating		2 x 4.5 kW
Electric Pump		3.7 kW
I.C. Engine power rating / Power (kW)		12.1 Hp / 9.2 kW
Battery / Batteries capacity		48 V / 300 Ah
Integrated charger (V / Ah)		48 V / 45 Ah
Miscellaneous		
Ground Pressure		12.73 daN/cm²
Hydraulic Pressure		200 Bar
Hydraulic tank capacity		12 l
Fuel tank		30 l
Vibration on hands/arms		< 2.5 m/s
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)

Load chart



Dimensional drawing




Equipment

Standard

230V Predisposition
 All-terrain, non-marking, foam-filled tyres
 Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
 Battery charge indicator lamp
 CAN bus technology
 Emergency stop button in platform and on frame
 Horn in the platform
 Hour meter
 Integrated diagnostic assistance
 Manual emergency lowering
 Multi-voltage integrated charger
 Negative-type braking on rear wheels
 Non-marking, foam-filled tyres
 Pendular arm
 Platform with open-work floor
 Proportional controls
 Protective cover for control panel
 Slings and securing rings
 Tool box in platform
 Traction battery

Optional

110 or 230V plug with differential circuit breaker
 Air predisposition
 Beep on every movement
 Beep upon travel
 Biodegradable oil
 Centralized recharging of battery
 Extreme cold oil
 Flashing Light
 Lockable fuel cap
 Personalized paintwork
 SMS : Safe Man System
 Safety harness
 Water predisposition
 Working headlight in platform



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508
RCS Nantes